



Compression Fogger CF 1-BM



Product highlights

- **✓** Effective treatment of all rooms
- ✓ Versatile use
- ✓ Feeding directly from any container
- ✓ Requires no power supply
- ✓ Simple operation
- ✓ Very fine and narrow drop spectrum
- ✓ Low noise emission



Finest fog without electricity

The fogger is a compact and powerful device that feeding the active ingredient directly from the customer's container. Only a compressed air supply is required for operation. The frame and the nozzles are made of high-quality stainless steel.

Thanks to its compact design, the CF1-BM is a highly versatile unit, which can either be mounted stationary on the wall or carried or driven mobile.

It is ideally suited for the following fields of application: Pest control, horticulture, stock protection, disinfection and especially for potato sprout control.

The CF 1-BM has two nozzles. If required the second nozzle can be switched off. Several units can easily be connected in series. It has an ON / OFF switch and can be extended with automatic control.

Technical Data

CF 1-BM	
Dimensions (LxWxH) [mm]	410 x330 x 520
Weight [kg]	8,3
Active substance Container size [I]	20
Diameter of dosage nozzle [mm]	1,1 (mounted) 0,6 (in accessories)
Output quantity [I/h] for water dosage nozzle 1,1 mm at 3 bars	up to 8
Values valid for fogging with water Droplet spectrum [µm] Dv(50) at 4 bar, nozzle 0,6 Dv(50) at 3 bar, nozzle 0,6 Dv(50) at 2 bar, nozzle 0,6 Dv(50) at 4 bar, nozzle 1,1 Dv(50) at 3 bar, nozzle 1,1 Dv(50) at 2 bar, nozzle 1,1 Air requirement [l/min] at 3 bar per nozzle	7 9 12 12 15 19
Operating pressure [bar]	1-6, typically 3
Operating conditions Ambient temperatur [°C]	- 10 to + 60
Noise emission [db(A)] Of one spray nozzle at 3 bar operating pressure	77





info@igeba.de

